



*Mastic Melter*  
**PRO PATCH 55**



- ① 4" MOLASSES VALVE
- ② CONTROL PANEL
- ③ ENGINE DRIVEN AGITATION
- ④ UTILITY HAND TORCH
- ⑤ BURNER ACCESS PORT

## PRO PATCH 55 MASTIC MELTER

- > 55 Gallon Capacity
- > Thermostatically Controlled
- > Triple Wall Construction
- > Compatible With Rubber or Mastic
- > Engine Driven Agitation
- > 60,000 BTU Output
- > Dimensions: 33"x87"x34"
- > Unloaded: 585 lbs. | Loaded: 1435 lbs.

### WHY USE ASPHALT MASTIC

Mastic is used for cracks and pavement defects that are 1.5" or larger. Mastic material is ideal when cracks are too wide for standard crack filling but too small for mill and fill. Mastic material offers an economical and efficient solution to pavement defects.

- > No compaction needed
- > Used on concrete and asphalt surfaces
- > Waterproof seal
- > Flexibility to expand and contract with surrounding pavement

## PRO PATCH 15 MASTIC APPLICATOR

- > 15 Gallon Capacity
- > Heavy Duty Steel Construction
- > 4" Flow Valve
- > 9" Horseshoe Screed
- > 50,000 BTU Burner



Ready to Buy or Have Additional Questions? 800-492-1757 | sales@kminternational.com

