

Badger

Fire Protection

ABC Dry Chemical



Badger's line of stored pressure multi-purpose dry chemical fire extinguishers are extremely versatile. They will tackle the majority of fire risks found in most commercial, industrial and domestic environments.

They are available in two versions, *BadgerExtra* our premium line and, *BadgerStandard* our value line.

Multi-purpose dry chemical is suitable for use on class A, B, and C fires. They mount on any surface with the wall hook supplied, or if preferred, can be supplied with optional vehicle bracket.

Features - *BadgerExtra*

- Available in four sizes, 2½ lb, 5 lb, 10 lb & 20 lb
- Chrome plated brass valves
- Stainless steel handle, lever, hose band and pull pin
- Color coded labels for instant type recognition
- Re-designed label incorporating easy to follow instructions and larger fire pictograms
- Epoxy coated steel cylinders to resist corrosion, dents and punctures
- 12 year interval between hydrotests
- 90% M.A.P.
- USCG approved

Features - *BadgerStandard*

- Available in four sizes, 2½ lb, 5 lb, 10 lb & 20 lb
- Aluminum valve, handle, lever and pull pin
- Epoxy coated steel cylinders to resist corrosion, dents and punctures
- 12 year interval between hydrotests
- 90% M.A.P.
- USCG approved

UL listed
Six year warranty



BadgerExtra



BadgerStandard

Specifications

BadgerStandard

Model Number	250MB-1	5MBH-6H	5MB-6HB	10MB-8H	20MB-6H
Nominal Capacity (lbs)	2.5	5	5	10	20
Nominal Capacity (kilograms)	1.13	2.27	2.27	4.54	9.07
UL Fire Rating	1A-10B:C	3A-40B:C	3A-40B:C	4A-80B:C	20A-120B:C
Agent Type	ABC	ABC	ABC	ABC	ABC
Item Part Number	22430	22435	22486	22603	22682
Valve Material	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum
Shell Material	Steel	Steel	Steel	Steel	Steel
Shipping weight (lbs)	5.4	10	10	17	33
Shipping weight (kilograms)	2.4	4.5	4.5	7.71	14.96
Operating Pressure	195 PSI	195 PSI	195 PSI	195 PSI	195 PSI
Temperature Range (°F)	-40° To 120°	-40° To 120°	-40° To 120°	-40° To 120°	-40° To 120°
Discharge Time (seconds)	9.5	14	14	22	28
Discharge Range (feet)	10 To 15	12 To 18	12 To 18	16 To 20	16 To 20
Discharge Range (meters)	3.14 to 4.6	3.7 to 5.5	3.7 to 5.5	4.9 to 6.1	4.9 to 6.1
Unit Height (inches)	14.87	15.25	15.25	18.94	21.13
Unit Height (centimeters)	37.78	38.7	38.7	48.1	53.67
Unit Width (inches)	5.5	7.25	7.25	7.75	9.25
Unit Width (centimeters)	13.97	18.41	18.41	19.68	23.49
Shell Diameter (inches)	3	4.25	4.25	5.25	7.25
Shell Diameter (centimeters)	7.62	10.8	10.8	13.33	18.41
USCG Approval	Yes	Yes	Yes	Yes	Yes
USCG Bracket	MB-250 Included	MB-5 Optional	MB-5 Included	UB-10 Optional	UB-20 Optional

BadgerExtra

Model Number	B250M	B250M-WH	B5M	B5M-B	B5M-1	B5M1-B	B10M	B10M-1	B20M
Nominal Capacity (lbs)	2.5	2.5	5	5	5	5	10	10	20
Nominal Capacity (kilograms)	1.13	1.13	2.27	2.27	2.27	2.27	4.54	4.54	9.07
UL Fire Rating	1A-10B:C	1A-10B:C	3A-40B:C	3A-40B:C	2A-10B:C	2A-10B:C	4A-80B:C	4A-80B:C	20A-120B:C
Agent Type	ABC	ABC	ABC	ABC	ABC	ABC	ABC	ABC	ABC
Item Part Number	23384	23462	23390	23463	23464	23466	23396	23467	23497
Valve Material	Plated Brass	Plated Brass	Plated Brass	Plated Brass	Plated Brass	Plated Brass	Plated Brass	Plated Brass	Plated Brass
Shell Material	Steel	Steel	Steel	Steel	Steel	Steel	Steel	Steel	Steel
Shipping weight (lbs)	5.4	5.8	10.4	10.4	10.4	10.4	18	18	33
Shipping weight (kilograms)	2.47	2.65	4.7	4.7	4.7	4.7	8.16	8.16	15
Operating Pressure	195 PSI	195 PSI	195 PSI	195 PSI	195 PSI	195 PSI	195 PSI	195 PSI	195 PSI
Temperature Range (°F)	-40°TO 120°	-40°TO 120°	-40°TO 120°	-40°TO 120°	-40°TO 120°	-40°TO 120°	-40°TO 120°	-40°TO 120°	-40°TO 120°
Discharge Time (seconds)	9.5	9.5	14	14	14	14	22	22	28
Discharge Range (feet)	10 TO 15	10 TO 15	12 TO 18	12 TO 18	12 TO 18	12 TO 18	16 TO 20	16 TO 20	16 TO 20
Discharge Range (meters)	(3.14-4.6)	(3.14-4.6)	(3.7-5.5)	(3.7-5.5)	(3.7-5.5)	(3.7-5.5)	(4.9-6.1)	(4.9-6.1)	(4.9-6.1)
Unit Height (inches)	14.875	14.875	15.25	15.25	15.25	15.25	18.94	19.13	21.13
Unit Height (centimeters)	37.78	37.78	38.7	38.7	38.7	38.7	48.1	48.59	53.67
Unit Width (inches)	5.5	5.5	7.25	7.25	7.25	7.25	7.75	8.13	9.25
Unit Width (centimeters)	13.97	13.97	18.41	18.41	18.41	18.41	19.68	20.65	23.49
Shell Diameter (inches)	3	3	4.25	4.25	4.25	4.25	5.25	5.25	7.25
Shell Diameter (centimeters)	7.62	7.62	10.8	10.8	10.8	10.8	13.33	13.33	18.41
USCG Approval	YES	YES	YES	YES	YES	YES	YES	YES	YES
USCG Bracket	MB-250 Included	MB-250 Optional	MB-5 Optional	MB-5 Included	MB-5 Optional	MB-5 Included	UB-10 Optional	UB-10 Optional	UB-20 Optional

BFPN0001

Badger

Fire Protection

4251 Seminole Trail
Charlottesville, VA 22911

Tel. (800) 446-3857

Fax. (800) 248-7809

www.badgerfire.com