

ION[™] Series

Super-LED® Lightheads

Engineered for optimal durability and versatility, the ultra compact ION Series provides high intensity warning or illumination. Models are available in a variety of sizes, optics, and configurations for every application.

ION Family Features

- SAE Class 1 Certified
- · Hard-coated lenses minimize environmental damage from the sun, salt, and road chemicals
- Go undercover with SAE Class 1 Certified Smoked lenses
- Synchronize to other Whelen sync products
- Five year warranty





WIONJ Universal mount



IONSMA Surface mount



Universal mount



Smoked lens

ION

Designed to mount in many applications, ION Series lightheads are available in directional or wide-angle models.

- Single or split color models
- TIR directional or wide-angle light spread models
- Available in universal or surface mount
- Universal mount models include combination permanent/ pedestal, clip, edge mounts, and double-sided tape, with a Black or White housing
- Universal mount options include bail/swivel bracket in Black or White, rubber grommet, and pedestal mount in Black or White
- Surface mount models include flange, available in Black, White, or Chrome

- Single color models have 25 Scan-Lock[™] flash patterns
- Split color models have 69 Scan-Lock flash patterns
- Supplied with 10" 4-wire pigtail
- Wide-angle surface mount lighthead meets NFPA 1901, KKK1822F requirements
- Amp draw: 0.40 amps (avg)
- Universal mount size: 1" (25mm) H x 1.25" (32mm) D x 4" (101mm) L
- Surface mount size: 1.69" (43mm) H x 1.13" (28mm) D x 5.94" (150mm) L

ION MODELS

| Universal Mount | | | |
|-----------------|--|--|--|
| ION* | Red, Blue, Amber, or White | | |
| ION# | Split, Amber/Blue, Amber/White, Blue/Red, or White/Red only, Clear lens | | |
| XON* | Red, Blue, Amber, or White, Smoked lens | | |
| XON# | Split, Amber/Blue, Amber/White, Blue/Red, or White/Red only, Smoked lens | | |

| Surface Mount | | | |
|--|---|--|--|
| IONSM* | Red, Blue, Amber, or White | | |
| IONSM# | Split, Amber/Blue, Amber/White, Blue/Red, or White/Red only, Clear lens | | |
| XONSM* | Red, Blue, Amber, or White, Smoked lens | | |
| XONSM# Split Amber/Blue, Amber/White, Blue/Red, or White/Red only, Smoked lens | | | |

| Wide-Angle Universal Mount | | | |
|--|---|--|--|
| WION* | Red, Blue, Amber, or White | | |
| WION# | Split, Amber/Blue, Amber/White, Blue/Red, or White/Red only, Clear lens | | |
| WXON* | Red, Blue, Amber, or White, Smoked lens | | |
| WXON# Split, Amber/Blue, Amber/White, Blue/Red, or White/Red only, Smoked lens | | | |

| Wide-Angle Surface Mount | | | |
|---|---|--|--|
| WIONSM* | Red, Blue, Amber, or White | | |
| WIONSM# | Split, Amber/Blue, Amber/White, Blue/Red, or White/Red only, Clear lens | | |
| WXONSM* | DNSM* Red, Blue, Amber, or White, Smoked lens | | |
| WXONSM# Split, Amber/Blue, Blue/Red, or White/Red only, Smoked lens | | | |

Replace symbol * in model number with letter indicating color desired: A = Amber, B = Blue, C = White, R = Red Replace # symbol in model number with letter indicating split color desired: D=Red/White, F=Amber/White, J=Red/Blue, K=Red/Amber, M=Blue/Amber. For White or Chrome housings, contact factory.

NEW ION™ T-Series™

The ION T-Series features advanced Linear Super-LED® optics in a sleek and low profile design, with a diameter of only .5".


- Available with SOLO[™] or DUO[™] (two color interleaved) technology and Linear Super-LED optics
- · Available in Amber, Blue, Red, and/or White
- · SOLO models are available in single or split colors
- SOLO single color models have 25 Scan-Lock™ flash patterns, split color models have 69
- DUO models have 33 Scan-Lock flash patterns
- · Easily surface mounts with two screws
- Includes Black flange and a 4-wire 6" (152mm) pigtail
- 12 VDC
- Amp draw:
 - o SOLO 0.33 amps (avg)
 - o DUO 0.28 amps (avg)
- Size: 1.50" (3.81cm) H, .50" (1.27cm) D, 5.14" (13.06cm) L

MODELS

| Clear Lens | | |
|------------|---|--|
| TLI* | Amber, Blue, Red, or White | |
| TLI# | Split Amber/Blue, Amber/White, Blue/White, Red/Blue or Red/White Only | |
| TLI2# | DUO Amber/Blue, Amber/White, Blue/White, Red/Blue or Red/White Only | |



| Smoked Lens | | | |
|--|---|--|--|
| TLI*X | TLI*X Amber, Blue, Red, or White | | |
| TLI#X | Split Amber/Blue, Amber/White, Blue/White, Red/Blue or Red/White Only | | |
| TLI2#X DUO Amber/Blue, Amber/White, Blue/White, Red/Blue or Red/White Only | | | |






ION™ DUO™ TRIO™ Features

ION DUO and TRIO lightheads feature two color or three color interleaved LEDs and advanced Linear Super-LED® optics

- · Available in Red, Blue, Amber, and White combinations
- · Available in universal or surface mount
- Universal mount includes combination permanent/pedestal, clip, edge mounts, double-sided tape, with a Black or White housing



Universal mount size: 1" (25mm) H x 1.25" (32mm) D x 4" (101mm) L

• Surface mount size: 1.69" (43mm) H x 2" (50mm) D x 5.94" (150mm) L

ION DUO Series

- Supplied with a 10" 5-wire pigtail
- Independent control of color one and color two
- 64 Scan-Lock flash patterns
- Amp draw (each color) 0.28 amps (avg)

ION TRIO Series

- Supplied with a 10" 6-wire pigtail
- · Choose from any combination of color one, color two, and/or color three
- · Color three features steady-burn override
- 25 Scan-Lock flash patterns
- Amp draw (each color) 0.40 amps (avg)

MODELS

| DUO Universal Mount | | |
|---------------------|--------------------------|--|
| I2J | Blue/Red | |
| I2F | Amber/White | |
| I2E | Blue/White | |
| I2D | Red/White | |
| I2M | Blue/Amber | |
| XI2J | Blue/Red, Smoked lens | |
| XI2F | Amber/White, Smoked lens | |
| XI2E | Blue/White, Smoked lens | |
| XI2D | Red/White, Smoked lens | |
| XI2M | Blue/Amber, Smoked lens | |
| | | |

| DUO Surface Mount | | | |
|-------------------|--------------------------|--|--|
| I2SMJ | Blue/Red | | |
| I2SMF | Amber/White | | |
| I2SME | Blue/White | | |
| I2SMD | Red/White | | |
| I2SMM | Blue/Amber | | |
| XI2SMJ | Blue/Red, Smoked lens | | |
| XI2SMF | Amber/White, Smoked lens | | |
| XI2SME | Blue/White, Smoked lens | | |
| XI2SMD | Red/White, Smoked lens | | |
| XI2SMM | Blue/Amber, Smoked lens | | |
| | | | |



| TRIO Universal Mount | | |
|----------------------|-------------------------------|--|
| I3JC | Red/Blue/White | |
| I3JA | Red/Blue/Amber | |
| I3KC | Red/Amber/White | |
| I3MC | Blue/Amber/White | |
| XI3JC | Red/Blue/White, Smoked lens | |
| XI3JA | Red/Blue/Amber, Smoked lens | |
| XI3KC | Red/Amber/White, Smoked lens | |
| XI3MC | Blue/Amber/White, Smoked lens | |

| TRIO Surface Mount | | | | |
|--------------------------------------|---------------------------------------|--|--|--|
| I3SMJC | Red/Blue/White | | | |
| I3SMJA | Red/Blue/Amber | | | |
| I3SMKC | Red/Amber/White | | | |
| I3SMMC | Blue/Amber/White | | | |
| XI3SMJC | Red/Blue/White, Smoked lens | | | |
| XI3SMJA | XI3SMJA Red/Blue/Amber, Smoked lens | | | |
| XI3SMKC Red/Amber/White, Smoked lens | | | | |
| XI3SMMC | XI3SMMC Blue/Amber/White, Smoked lens | | | |
| | | | | |

Replace symbol * in model number with letter indicating color desired: $A = Amber, \ B = Blue, \ C = White, \ R = Red$

Replace # symbol in model number with letter indicating split color desired: D=Red/White, E=Blue/White, F=Amber/White, J=Red/Blue, M=Blue/Amber For White or Chrome housings, contact factory.



ION™ V-Series™

Utilizing multiple planes of light in one lighthead, the ION V-Series is available in three-in-one combination or single color warning models.



- Single color models have combination 180° and TIR directional warning
- · Available in universal or surface mount
- Universal mount models include combination permanent/pedestal mount, clip, edge mounts, and double-sided tape. Options include bail/ swivel bracket in Black or White, pedestal mount in Black or Chrome, and rubber grommet
- Surface mount models include flange, available in Black, White, or Chrome
- Warning segment has 25 Scan-Lock™ flash patterns
- Warning segment available in Red, Amber, Blue, or White
- 6" pigtail with sync wire allows up to eight lightheads to be synchronized together for the warning segment of the lighthead
- 12 VDC
- Amp draw:
 - Combination model Warning lights 0.76 amps (avg),
 Alley lights 0.31 amps (avg), Puddle lights 0.12 amps (avg)
- Single color warning model 1.147 amps (avg)
- Universal mount size: 1" (25mm) H x 2.19" (56mm) D x 4.06" (104mm) L
- Surface mount size: 1.69" (43mm) H x 2" (50mm) D x 5.94" (150mm) L







Surface mount IONSV3C

MODELS

| V-Series Universal Mount | | Housing | V-Series Surface Mount | | Housing |
|--------------------------|--|---------|------------------------|---|---------|
| IONV3* | Combination, Red, Blue, Amber, or White | Black | IONSV3* | Combination, Red, Blue, Amber, or White | Black |
| IONV1* | Single Color, Red, Blue, Amber, or White | Black | IONSV3*C | Combination, Neu, Blue, Amber, or White | Chrome |
| XONV3* | Combination, Red, Blue, Amber, or White, | Black | IONSV1* | Single Color, Red, Blue, Amber, or White | Black |
| 7101110 | Smoked lens | 2.00.1 | IONSV1*C | Siligle Color, Neu, Blue, Alliber, or Willie | Chrome |
| XONV1* | Single Color, Red, Blue, Amber, or White, Smoked lens | Black | XONSV3* | Combination, Red, Blue, Amber, or White, Smoked lens | Black |
| | 1 | | XONSV1* | Single Color, Red. Blue, Amber, or White, Smoked lens | Black |

Replace symbol * in model number with letter indicating color desired: A = Amber, B = Blue, C = White, R = Red, for White housings, contact factory.





OPTIONS

ION Series

| IONK1B | Swivel mount bracket, Black | | | |
|---------|---|--|--|--|
| IONGROM | Grommet mount kit, Black | | | |
| IONPEDB | Pedestal mount kit, Black | | | |
| IONBKT1 | Universal license plate bracket, horizontal mount, Black. For 2 ION Series lightheads, not for use with ION V-Series | | | |
| IONBKT2 | 2013-2016 Ford Police Interceptor Utility, rear hatch mounting brackets (pair), Black. Requires 6 ION Series lightheads, purchased separately | | | |
| IONBKT4 | 2013-2016 Ford Police Interceptor Utility, rear hatch mounting brackets (pair), Black. Requires 2 ION Series lightheads, purchased separately | | | |
| IONBKT5 | Universal mount, reversed. Remove screws without removing the light | | | |
| IONBKT6 | 2015-2018 Chevy Tahoe, rear hatch mounting brackets (pair), Black. Requires 2 ION Series lightheads, purchased separately | | | |
| IONBKT7 | 2015-2018 Chevy Tahoe, grille mount bracket. Requires 2 ION Series lightheads, purchased separately | | | |

Whelen Engineering reserves the right to upgrade and improve products without notice.

© 2018 Whelen Engineering Company, Inc. Printed in U.S.A. NASCAR® is a registered trademark of the National Association for Stock Car Auto Racing, Inc. Code No. 12431K - 03/16/2018

ION T-Series™

| TIONFC | T-Series Chrome Flange |
|----------|---|
| TIONBKT1 | T-Series "L" mounting bracket for 1 lighthead |
| TIONBKT2 | T-Series Universal license plate bracket for 2 lightheads |
| TIONBKT3 | T-Series "L" mounting bracket for 2 lightheads |
| TIONBKT4 | T-Series Universal over/under "L" mounting bracket for 2 lightheads |



51 Winthrop Road Chester, Connecticut 06412-0684 (860) 526-9504 www.whelen.com

